SPARTAN CARGO TRAILERS

Model	4x6SA	5x8SA	5x10SA	6X8SA	6X10SA	6X12SA	6X14SA	7X12SA	7X14SA
Exterior Overall Length (Inches)		140	164	145	169	193	217	196	220
Exterior Overall Width (Inches)		80.5	80.5	92.5	92.5	92.5	92.5	103	103
Exterior Overall Height (Inches)		78	78	96	96	96	96	97	97
Interior Width (Inches)		57	57	68	68	68	68	81.5	81.5
Interior Length (V-NOSE) (Inches)		113	137	113	137	161	185	164	188
Interior Height (Inches)		60	60	78	78	78	78	78	78
Height from Ground (Inches)		13	13	13	13	13	13	13	13
Tire Size	175-75-13	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15
Tire Type	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Wheel Type	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel
Hitch Ball Size	2"	2"	2"	2"	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		15	15	15	15	15	15	15	15
Curb Weight (STD Trailer)	750	1060	1110	1340	1440	1540	1640	1780	1880
GVWR	2000	2990	2990	2990	2990	2990	2990	2990	2990
Payload (approx)	1250	1930	1880	1650	1550	1450	1350	1210	1110
Rear Door Type	Single Swing	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Width		49.5	49.5	65	65	65	65	65	65
Rear Door Opening Height		54.5	54.5	73	73	73	73	73	73
Side Door Width	36"	36"	36"	36"	36"	36"	36"	36"	36"
Side Door Height	74"	74"	74"	74"	74"	74"	74"	74"	74"
12V Plug Connection	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY
Floor Thickness	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Wall Thickness	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Floor Crossmember Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"
Wall Stud Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"
Roof Bow Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"
Floor Crossmember Type	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel
Wall Stud Type	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube
Roof Bow Type	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube
Floor Interior Type	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck
Wall Interior Type	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood
Exterior Guage Metal	0.024	0.024	0.024	0.024	0.024	0.024	0.024	0.024	0.024

SPARTAN CARGO TRAILERS

Model	6x12TA	6x14TA	7x12TA	7x14TA	7X16TA	7x18TA	7X20TA
Exterior Overall Length (Inches)	193	217	196	220	244	268	292
Exterior Overall Width (Inches)	92.5	92.5	103	103	103	103	103
Exterior Overall Height (Inches)	96	96	97	97	99	99	99
Interior Width (Inches)	68	68	81.5	81.5	81.5	81.5	81.5
Interior Length (V-NOSE) (Inches)	161	185	164	188	212	236	260
Interior Height (Inches)	78	78	78	78	78	78	78
Height from Ground (Inches)	13	13	13	13	13	13	13
Tire Size	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15
Tire Type	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Wheel Type	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball (Inches)	15	15	15	15	15	15	15
Curb Weight (STD Trailer)	1900	2230	2100	2380	2540	2740	2940
GVWR	7000	7000	7000	7000	7000	7000	7000
Payload (approx)	5100	4770	4900	4620	4460	4260	4060
Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Width	65	65	76.75	76.75	76.75	76.75	76.75
Rear Door Opening Height	73	73	73	73	73	73	73
Side Door Width	36"	36"	36"	36"	36"	36"	36"
Side Door Height	74"	74"	74"	74"	74"	74"	74"
12V Plug Connection	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY
Floor Thickness	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Wall Thickness	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Floor Crossmember Spacing	16"	16"	16"	16"	16"	16"	16"
Wall Stud Spacing	16"	16"	16"	16"	16"	16"	16"
Roof Bow Spacing	16"	16"	16"	16"	16"	16"	16"
Floor Crossmember Type	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel
Wall Stud Type	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube
Roof Bow Type	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube
Floor Interior Type	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck
Wall Interior Type	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood
Exterior Guage Metal	0.024	0.024	0.024	0.024	0.024	0.024	0.024

SPARTAN CARGO TRAILERS

Model	8.5x14TA	8.5x16TA	8.5x18TA	8.5x20TA	8.5x22TA	8.5x24TA	8.5X26TA	8.5X28TA	8.5X30TA	8.5X32TA	8.5X34TA
Exterior Overall Length (Inches)	220	244	268	290	314	334	358	382	406	430	454
Exterior Overall Width (Inches)	102	102	102	102	102	102	102	102	102	102	102
Exterior Overall Height (Inches)	99	99	99	99	99	99	100	100	100	103	103
Interior Width (Inches)	96	96	96	96	96	96	96	96	96	96	96
Interior Width in Wheel Wheels (Inches)	83	83	83	83	83	83	83	83	83	83	83
Interior Length (Inches)	183	207	231	256	280	303	326	349	372	395	418
Interior Height (Inches)	78	78	78	78	78	78	78	78	78	78	78
Height from Ground (Inches)	13	13	13	13	13	13	14	14	14	15	15
Tire Size	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	205-75-15	225-75-15	225-75-15	225-75-15	235-80-16	235-80-16
Tire Type	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Wheel Type	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel	Grey Steel
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball (Inches)	19	19	19	19	19	19	20	20	20	21	21
Curb Weight (STD Trailer)	2840	2950	3060	3240	3375	3640	4160	4360	4560	6800	7000
GVWR	7000	7000	7000	7000	7000	7000	9990	9990	9990	14000	14000
Payload (approx)	4160	4050	3940	3760	3625	3360	5830	5630	5430	7200	7000
Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Width (Inches)	88	88	88	88	88	88	88	88	88	88	88
Rear Door Opening Height (Inches)	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5	75.5
Side Door Width	36"	36"	36"	36"	36"	36"	36"	36"	36"	36"	36"
Side Door Height	74"	74"	74"	74"	74"	74"	74"	74"	74"	74"	74"
12V Plug Connection	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY	7-WAY
Floor Thickness	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Wall Thickness	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Floor Crossmember Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"
Wall Stud Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"
Roof Bow Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"
Floor Crossmember Type	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel	C-Channel
Wall Stud Type	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube
Roof Bow Type	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube	1"x1-1/2" Tube
Floor Interior Type	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck	Stable Deck
Wall Interior Type	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood	BC Plywood
Exterior Guage Metal	0.024	0.024	0.024	0.024	0.024	0.024	0.030	0.030	0.030	Polycore	Polycore